

HS-XVR16101-L8



قابلیت های کلیدی

- یک عدد HDMI و یک عدد VGA
- پشتیبانی از 2 عدد هارد تا ظرفیت 8 ترابایت برای هر کدام
- قابلیت بروزرسانی آنلاین
- پشتیبانی از سیگنال های تصویر TVI, AHD, CVI, CVBS, IP
- 16 کانال ورودی آنالوگ تا رزولوشن 8 مگاپیکسل
- 8 کانال IP تا رزولوشن 8 مگاپیکسل (تا 24 کانال فقط IP)
- پشتیبانی از دوربین های با پروتکل ONVIF

Specifications

Analog Video Input	16-ch, BNC
IP Video Input	8 -ch(only IP up to 24ch), each channel up to 8MP
Supported Analog Camera Types	Support AHD input: 8MP@15fps 5MP@20fps 4MP@30fps 1080P@30fps 720P@60fps Support TVI input: 8MP@15fps 5MP@20fps 4MP@30fps 1080P@30fps 720P@60fps Support CVI input: 8MP@15fps 5MP@25fps 4MP@30fps 1080P@30fps 720P@30fps Support CVBS input
Audio Input	1-ch, RCA
Audio Compression	G.711U
CVBS Output	1-ch, BNC
VGA Output	1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
HDMI Output	4K(3840x2160)30Hz, 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
Audio Output	1-ch, RCA
Synchronous Playback	16
Live view display	HDMI/VGA: 1/4/6/8/9/16/25
Two-way Audio	1-ch, RCA
FTP/Schedule/E vent Snapshot	16-ch snapshot, up to 704*576 resolution
Incoming Bandwidth	80Mbps (Up to 112Mbps after all analog channel conversion)
Outgoing Bandwidth	160Mbps
Remote Users	128
Protocols	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SMTP
Browser	IE(IE10/11) for Windows Firefox (version 52.0 and above) for Windows Chrome(version 45 and above) for Windows Edge (version 79 and above) for Windows

Recording Resolution	8MP Lite/5MP Lite/4MP Lite/1080P/720P/D1	
Recording Frame Rate	MAIN STREAM	SUB STREAM
	8MP Lite@8fps	D1@8fps
	5MP Lite @12fps	D1@12fps
	4MP Lite@15fps	D1@12fps
	1080P@15fps	D1@12fps
	720p@30fps	D1@12fps
Audio Sample Rate	8KHz, 16 bit per channel	
Audio Bit Rate	64Kbps per channel	
Capability	Analog: 16 x 8MP Lite@8, 16x 5MP Lite@12, 16x 4MP Lite@15, 16x 1080P@15, 16 x 720@30 IP: 24 x D1@30, 16 x 720P@30, 8 x 1080P@30	
SATA	2 SATA interface	
Capacity	Up to 8TB for each HDD (The maximum HDD capacity varies with environment temperature)	
VCA Detection	Ultra Motion Detection(UMD) for analog:8-ch	
VCA Search	Behavior Search	
General Alarm	Motion detection	
Alert Alarm	IP Conflict, Network Disconnected, Disk offline, Disk Abnormal, Illegal Access, Hard Disk Space Low, Hard Disk Full, Recording/Snapshot Abnormal	
Network Interface	1 RJ45 10M/100M/1000M self-adaptive Ethernet Interface	
USB Interface	Rear panel: 1 x USB3.0, Front panel: 1xUSB2.0	
Serial Interface	1 x RS485	
Alarm In	4	
Alarm Out	1	
Power Supply	12V DC Power Consumption: ≤ 12 W(without HDD)	
Working Environment	- 10°C ~ + 55°C (+ 14°F ~ + 131°F), Humidity ≤ 90% RH(non-condensing)	
Dimensions(W×D×H)	380mm × 326mm × 53mm (15.0" × 12.8" × 2.1")	
Weight (without HDD)	≤ 2.0 Kg (4.4lb)	
Certification	UL / CE / FCC / RoHS / WEEE	

Dimensions

