

HS-XVR4101-L8



قابلیت های کلیدی

- یک عدد HDMI و یک عدد VGA
- پشتیبانی از 1 عدد هارد تا ظرفیت 8 ترابایت
- قابلیت بروزرسانی آنلاین

- پشتیبانی از سیگنال های تصویر TVI, AHD, CVI, CVBS, IP
- 4 کانال ورودی آنالوگ تا رزولوشن 8 مگاپیکسل
- 2 کانال IP تا رزولوشن 4 مگاپیکسل (تا 6 کانال فقط IP)
- پشتیبانی از دوربین های با پروتکل ONVIF

Specifications

Analog Video Input	8-ch, BNC
IP Video Input	4-ch(only IP up to 12ch), each channel up to 8MP
Supported Analog Camera Types	Support AHD input: 8MP@15fps 5MP@20fps 4MP@30fps 1080P@30fps 720P@30fps Support TVI input: 8MP@15fps 5MP@20fps 4MP@30fps 1080P@30fps 720P@30fps Support CVI input: 8MP@15fps 5MP@25fps 4MP@30fps 1080P@30fps 720P@30fps Support CVBS input
Audio Input	1-ch, RCA
Audio Compression	G.711U
CVBS Output	1-ch, BNC
VGA Output	1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
HDMI Output	3840 x 2160/30Hz, 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
Audio Output	1-ch, RCA
Synchronous Playback	8
Live view display	HDMI/VGA: 1/4/6/8/9/16
Two-way Audio	1-ch, RCA
FTP/Schedule/E vent Snapshot	8-ch snapshot, up to 704*576 resolution
Incoming Bandwidth	40Mbps (Up to 56Mbps after all analog channel conversion)
Outgoing Bandwidth	64Mbps
Remote Users	128
Protocols	TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP
Browser	IE(IE10/11) for Windows Firefox (version 52.0 and above) for Windows Chrome(version 45 and above) for Windows Edge (version 79 and above) for Windows

Recording Resolution	8MP Lite/5MP Lite/4MP Lite/ 1080P/720P/CIF	
Analog Video Input	Main stream	Sub stream
	8MP Lite@8fps	D8@1fps
	5MP Lite@12fps	D1@12fps
	4MP Lite@15fps	D1@15fps
	1080P@15fps	D1@15fps
	720p@30fps	D30z@1fps
Audio Sample Rate	8KHz,16 bit per channel	
Audio Bit Rate	64Kbps per channel	
Capability	Analog: 8 x 8MP Lite@8 ,8x 5MP Lite@12 ,8x 4MP Lite@15 ,8x 1080P@15 IP: 1 x 8MP@30,2 x 4MP @30,4 x 1080P@30	
SATA	1 SATA interface	
Capacity	Up to 8TB for each HDD (The maximum HDD capacity varies with environment temperature)	
VCA Detection	Ultra Motion Detection(UMD) for analog:8-ch	
VCA Search	Behavior Search	
General Alarm	Motion detection	
Alert Alarm	IP Conflict, Network Disconnected, Disk offline, Disk Abnormal, Illegal Access, Hard Disk Space Low, Hard Disk Full, Recording/Snapshot Abnormal	
Network Interface	1 RJ45 10M/100M self-adaptive Ethernet Interface	
USB Interface	Rear panel: 2 x USB2.0	
RS485	1	
Alarm In	4-ch	
Alarm Out	1-ch	
Power Supply	12V DC Power Consumption: ≤ 10 W (without HDD)	
Working Environment	- 10℃ ~ + 55℃ (+ 14°F ~ + 131°F) , Humidity ≤ 90% RH(non-condensing)	
Dimensions(W×D×H)	260mm ×226mm× 47mm (10.2"× 8.9" × 1.8")	
Weight (without HDD)	≤1.1 Kg (2.42lb)	
Certification	UL /CE /FCC /RoHS /WEEE	

Dimensions

