

HS-XVR8101-L8



قابلیت های کلیدی

- یک عدد HDMI و یک عدد VGA
- پشتیبانی از 1 عدد هارد تا ظرفیت 8 ترابایت
- قابلیت بروزرسانی آنلاین

- پشتیبانی از سیگنال های تصویر TVI, AHD, CVI, CVBS, IP
- 8 کانال ورودی آنالوگ تا رزولوشن 8 مگاپیکسل
- 4 کانال IP تا رزولوشن 4 مگاپیکسل (تا 12 کانال فقط IP)
- پشتیبانی از دوربین های با پروتکل ONVIF

Specifications

Analog Video Input	4-ch, BNC	8-ch, BNC
IP Video Input	2-ch(only IP up to 6ch), each channel up to 4MP	4-ch(only IP up to 12ch), each channel up to 8MP
Supported Analog Camera Types	Support AHD input: 8MP@15fps 5MP@20fps 4MP@30fps 1080P@30fps 720P@30fps Support TVI input: 8MP@15fps 5MP@20fps 4MP@30fps 1080P@30fps 720P@30fps Support CVI input: 8MP@15fps 5MP@25fps 4MP@30fps 1080P@30fps 720P@30fps Support CVBS input	SUPPORT AHD INPUT: 8MP@15fps 5MP@20fps 4MP@30fps 1080P@30fps 720P@30fps SUPPORT TVI INPUT: 8MP@15fps 5MP@20fps 4MP@30fps 1080P@30fps 720P@30fps SUPPORT CVI INPUT: 8MP@15fps 5MP@25fps 4MP@30fps 1080P@30fps 720P@30fps SUPPORT CVBS INPUT
Audio Input	1-ch, RCA	
Audio Compression	G.711U	
CVBS Output	1-ch, BNC	
VGA Output	1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz	
HDMI Output	3840 x 2160/30Hz, 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz	
Audio Output	1-ch, RCA	
Synchronous Playback	4	8
Live view display	HDMI/VGA: 1/4/6/8/9	HDMI/VGA: 1/4/6/8/9/16
Two-way Audio	1-ch, RCA	
FTP/Schedule/E vent Snapshot	4-ch snapshot, up to 704*576 resolution	8-ch snapshot, up to 704*576 resolution
Incoming Bandwidth	40Mbps (Up to 48Mbps after all analog channel conversion)	40Mbps (Up to 56Mbps after all analog channel conversion)
Outgoing Bandwidth	48Mbps	64Mbps
Remote Users	128	
Protocols	TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP	
Browser	IE(IE10/11) for Windows Firefox (version 52.0 and above) for Windows Chrome(version 45 and above) for Windows Edge(version 79 and above) for Windows	

Recording Resolution	8MP Lite/5MP Lite/4MP Lite/1080P/720P/CIF		8MP Lite/5MP Lite/4MP Lite/1080P/720P/CIF
Recording Frame Rate	Main stream	D1@8fps	Main stream
	8MP Lite@8fps	D1@8fps	8MP Lite@8fps
	5MP Lite @12fps	D1@12fps	5MP Lite@12fps
	4MP Lite@15fps	D1@15fps	4MP Lite@15fps
	1080P@15fps	D1@15fps	1080P@15fps
Audio Sample Rate	8KHz, 16 bit per channel		
Audio Bit Rate	64Kbps per channel		
Capability	Analog: 4 x 8MP Lite@ 8, 4x 5MP Lite@12, 4x 4MP Lite@15, 4 x 1080P@15		Analog: 8 x 8MP Lite@8, 8x 5MP Lite@12, 8x 4MP Lite@15, 8x 1080P@15
	IP: 1 x 4MP@30, 2 x 1080P@30		IP: 1 x 8MP@30, 2 x 4MP@30, 4 x 1080P@30
SATA	1 SATA interface		
Capacity	Up to 8TB for each HDD (The maximum HDD capacity varies with environment temperature)		
VCA Detection	Ultra Motion Detection(UMD) for analog-4-ch		Ultra Motion Detection(UMD) for analog-8-ch
VCA Search	Behavior Search		
General Alarm	Motion detection		
Alert Alarm	IP Conflict, Network Disconnected, Disk offline, Disk Abnormal, Illegal Access, Hard Disk Space Low, Hard Disk Full, Recording/Snapshot Abnormal		
Network Interface	1 RJ45 10M/100M self-adaptive Ethernet Interface		
USB Interface	Rear panel: 2 x USB2.0		
RS485	1		
Alarm In	4-ch		
Alarm Out	1-ch		
Power Supply	12V DC Power Consumption: ≤ 10 W (without HDD)		
Working Environment	- 10°C ~ + 55°C (+ 14°F ~ + 131°F), Humidity ≤ 90% RH(non-condensing)		
Dimensions(W×D×H)	260mm × 226mm × 47mm (10.2" × 8.9" × 1.8")		
Weight (without HDD)	≤ 1.1 Kg (2.42lb)		
Certification	UL / CE / FCC / RoHS / WEEE		

Dimensions

